



**Declaration Of Performance
CPR-IT4/B162A REV.02**

1. Unique identification Code of the product type:

DAKBASE 460P60

2. Intended use(s) of the construction product:

Flexible sheets for waterproofing.

3. Manufacturer:

**POLYGLASS S.P.A VIA DELL'ARTIGIANATO, 34 31047 PONTE DI PIAVE (TV) ITALY
www.polyglass.it**

4. Authorised representative:

Not applicable

5. System(s) of assessment and verification of constancy of performance of the product (AVCP):

System 2+

6a. Harmonized standard:

EN 13707:2004 +A2:2009

Notified Body:

The notified Bureau Veritas, No. 1370, carried out the initial inspection of the factory and production control factory and the continuous monitoring, assessment and verification of factory production control, and issued the certificate of conformity of factory production control.

6b. European Assessment Document

Not applicable



POLYGLASS SPA

Sede Legale/Registered Office: Viale Jenner, 4 - 20159 MILANO

Sede Amministrativa/Head Office: Via dell'Artigianato, 34 -31047 Ponte di Piave (TV)

Tel. +39 04227547 - Fax +39 0422854118 www.polyglass.com - E-mail: info@polyglass.it

7. Declared performance

Essential characteristics	Units	Performance	Harmonised technical specification
EXTERNAL FIRE PERFORMANCE	Class	NPD	EN 13707:2004 + A2 :2009
REACTION TO FIRE	Class	NPD	
WATERTIGHTNESS	kPa	Pass	
TENSILE STRENGTH: maximum tensile force LxT* elongation at maximum tensile force LxT*	N/50 mm %	500 x 300 (-20%) 30 x 30 (-15%)	
ROOT RESISTANCE	-	NPD	
RESISTANCE TO STATIC LOADING method A	Kg	≥ 10	
Resistance to impact method A	mm	≥ 400	
RESISTANCE TO TEARING LxT*	N	150 X 150 (-30%)	
JOINT STRENGTH Peel resistance of joints Shear resistance of joints	N/50 mm N/50mm	NPD NPD	
DURABILITY UV HEAT AND WATER Heat flow after heat oven exposure Pliability after heat oven exposure	- °C °C	≥ 100 NPD	
DURABILITY (after QUV test) Visible defects	-	NPD	
PLIABILITY	°C	≤ -5	
DANGEROUS SUBSTANCES	-	See note 2	

* L means longitudinal direction, T means transverse direction

Note 2 National regulations on dangerous substances may require verification and declaration on release, and sometimes content, when construction products covered by this standard are placed on those markets. This product does not contain asbestos or tar constituents.

8. Appropriate technical documentation and / or technical specification documents

Not applicable

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of responsibility is issued in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Polyglass S.p.A, 05/06/2018

Signed by CEO:

Ing. P. Ciferri

